


DPL™ Super Series™

Specifications



Models	DPL-25S		DPL-30S		DPL-35S	
Measurements	US	Metric	US	Metric	US	Metric
Working height*	31 ft 4 in	9.5 m	36 ft	11.14 m	40 ft 10 in	12.62 m
Platform height	25 ft 4 in	7.70 m	30 ft	9.14 m	34 ft 10 in	10.62 m
Height - stowed	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m	6 ft 6 in	1.98 m
Length - stowed	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m	6 ft 10 in	2.08 m
Width	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m	2 ft 7.5 in	.80 m

Productivity

Lift capacity:ANSI/CSA/CE	750 lbs	340 kg	750 lbs	340 kg	600 lbs	272 kg
---------------------------	---------	--------	---------	--------	---------	--------

ANSI/CSA

Outrigger footprint:

A length	7 ft 2 in	2.11 m	7 ft 6 in	2.29 m	7 ft 6 in	2.29 m
B width	4 ft 8.5 in	1.44 m	5 ft 8 in	1.73 m	5 ft 8 in	1.73 m
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m

CE

Outrigger footprint:

A length	6 ft 10 in	2.08 m	7 ft 2.25 in	2.19 m	7 ft 2.25 in	2.19 m
B width	4 ft 8.5 in	1.44 m	5 ft 8.75 in	1.75 m	5 ft 8.75 in	1.75 m
C corner access	1 ft 5 in	.43 m	2 ft	.61 m	2 ft	.61 m
D wall access front	7 in	.18 m	9 in	.23 m	9 in	.23 m
E wall access side	1 ft 4 in	.41 m	1 ft 10 in	.56 m	1 ft 10 in	.56 m

Platform length	6 ft	1.83 m	6 ft	1.83 m	6 ft	1.83 m
Platform width	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m	2 ft 3.5 in	.70 m

Power

Power source: AC models	110 V / 50-60 Hz or 220 V / 50-60 Hz
DC models	12 V

Weight**

ANSI/CSA (AC)	1,371 lbs	622 kg	1,474 lbs	669 kg	1,574 lbs	714 kg
ANSI/CSA (DC)	1,481 lbs	672 kg	1,584 lbs	718 kg	1,684 lbs	764 kg
AUS/CE (AC)	1,371 lbs	622 kg	1,474 lbs	669 kg	1,645 lbs	746 kg
AUS/CE (DC)	1,481 lbs	672 kg	1,584 lbs	718 kg	1,755 lbs	796 kg

Standards Compliance

ANSI A92.3, CSA B354.1, EN 280, AS 1418.10

* The metric equivalent of working height adds 2 m to platform height. U.S. adds 6 ft to platform height.

** Weight will vary depending on options and/or country standards

Features

Standard Features

Measurements

DPL-25S

- 31 ft 4 in (9.55 m) working height
- 25 ft 4 in (7.72 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

DPL-30S

- 36 ft (10.97 m) working height
- 30 ft (9.14 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 750 lbs (340 kg) lift capacity

DPL-35S

- 40 ft 10 in (12.62 m) working height
- 34 ft 10 in (10.62 m) platform height
- 2 ft 7.5 in (.80 m) base width
- Up to 600 lbs (272 kg) lift capacity

Productivity

- Large platform with room for 2 workers
- Auxiliary platform lowering
- Most rigid mast in the industry
- Durable base system
- Easily rolls through standard doorways
- AC power to platform
- Dual activated up/down switch
- Ground fault interrupt lower receptacle
- Patented outrigger interlock system
- Outrigger storage sockets
- Swivel-lock caster
- Tie down attachment points
- Forklift pocket access on all sides
- Angled entry ladder
- LED lights indicate outrigger installation
- Winch attachment points
- Locking key switch

Power

- DC models include a 15 amp charging system with 110V / 50-60 Hz or 220V / 50-60 Hz input voltage

Options & Accessories

Productivity

- Operational warning light and descent alarm package (mandatory for CE and AUS)
- Tool tray
- Fluorescent tube caddy
- Platform locating laser light

Platform

- 6ft x 2ft 3in (1.83 m x .69 m)

Power

- AC power 110V / 50-60 Hz
- AC power 220V / 50-60 Hz
- DC power 12V 190 Amp battery



CO.MA.CO S.r.l.

via XIV Strada 21 - 20020 Cesate (MI) - Italy

Tel. +39 02 99065169

info@comacopro.com

www.comacopro.com